



CALCUATING BASIC COATINGS® WATERBASED FINISHES FOR GYM RECOATING

SCHOOL _____
GYM LOCATION _____ SQUARE FOOTAGE OF GYM _____

For periodic recoating, apply two coats of *Player's Choice® Premier* or *StreetShoe®* to the entire floor. If needed, apply an additional coat to high traffic areas such as keys **before** applying the two coats to the entire floor.

SUPPLIES

Squeaky Cleaner - 2 Gallon Per 10,000 Square Feet	Total Gallons _____
Intensive Floor Treatment – 2 Gallon Per 10,000 Square Feet	Total Gallons _____
Towels (For Cleaning) - 3 Towels Per 1,000 Square Feet	Towels _____
Towels (For Dusting) - 2 to 4 Towels Per Gym	Towels _____
	Total Towels _____
Screens (New 100/ 120-Grit) - 1 screen per 500 sq. ft.	Total Screens _____
TyKote® – 1 gallon per 2,500 sq. ft.	Total Gallons _____

FINISH

<i>Player's Choice® Premier</i>	Gallons	<i>StreetShoe®</i>	Gallons
1st Coat (500 sq.ft./gl)	_____	1st Coat (500 sq.ft./gl)	_____
2nd Coat (700 sq.ft./gl)	_____	2nd Coat (700 sq.ft./gl)	_____
		Total Gallons Needed	_____
		Total Refills	_____

Applicator Refills - 1 per gym

TOOLS NEEDED

Buffer With Drive Pad	Rayon string mop for TyKote® application
Non-marking extension cord	Scrapers
Vacuum With Protected Pick-Up Wand	Wide push broom
T-Bar applicator	Mop bucket with wringer (2)
Polishing/buffing/stringing pads-white, red, Brown, black	

General Notes - Have all workers wear non-marking shoes. Use towels at doorways to wipe feet going in and out of the gym. Train personnel in the safe and proper use of Basic Coatings XL Catalyst.

LONG TERM FLOOR MAINTENANCE

Squeaky Cleaner - Use weekly or more frequently as needed.