



Daily

Tack Cleaning

Dry tack with microfiber mops regularly. Combine a diluted solution of **Squeaky**™ cleaner with microfiber mops or white cotton bath towels. **Squeaky** floor cleaner is an excellent choice for streak-free routine cleaning of dirt, grease and scuffs.

- ◆ Soak several large bath towels in the solution. Wring them out until damp.
- ◆ Wrap a damp towel around the head of a push broom and push across the floor. To prevent redeposit of dirt and oil, refold towel using clean sides. Clean the entire floor using a clean, damp towel as needed.

Periodically

Maintenance Cleaning with an Autoscrubber

Squeaky cleaner will remove dirt and body oils without leaving a residue.

- ◆ Use white or blue floor pads with a light head pressure.
- ◆ Scrub the floor with **Squeaky** cleaner solution. (1 part **Squeaky** : 4 parts water)

Aggressive Cleaning with an Autoscrubber

The combination of **I.F.T. (Intensive Floor Treatment)** and **Squeaky** cleaners can be used to clean heavy soils and contaminants.

- ◆ Use white or blue floor pads with a light head pressure.
- ◆ Spot clean trouble areas with a non-aggressive pad and **I.F.T.** solution. Always rinse with **Squeaky**.
- ◆ Scrub the floor with **I.F.T.** solution (1 part **I.F.T.** : 4 parts water)
- ◆ Rinse with **Squeaky** cleaner solution. (1 part **Squeaky** : 4 parts water)

Autoscrubber Tips

- ◆ Do not use excessive cleaning fluid (no puddling).
- ◆ Check for good operating squeegees.
- ◆ Do not use a pad that has been used on other floors in the facility.
- ◆ Thoroughly rinse out the solution tank before adding cleaning solution.
- ◆ If you notice crowning or cupping, stop autoscrubbing the floor.

Recoating

Most sports floors should be recoated on an annual basis. Recoat when the original film is showing signs of wear but before the finish has worn down to the bare wood. The **TyKote® Dust-Free Refinishing System** may be used annually to recoat your sports floor.

- ◆ Autoscrub with **I.F.T.** solution.
- ◆ Autoscrub with **Squeaky** cleaner solution.
- ◆ Apply **TyKote**.
- ◆ Coat with **StreetShoe® Waterbased Wood Floor Finish**.



For more information,
contact your
BasicSports distributor.
Call us toll-free,
800-441-1934.
Or visit our website at
www.basiccoatings.com.



General Maintenance Tips

- ◆ DO NOT USE CLEANERS ON NEWLY FINISHED FLOORS FOR AT LEAST 30 DAYS.
- ◆ Always clean up any liquid spills immediately.
- ◆ Use entrance matting at all doorways and keep vacuumed.
- ◆ Avoid scratching the floor when moving equipment.
- ◆ Only clean athletic shoes should be allowed on the floor.
- ◆ Maintain indoor relative humidity between 35 and 50 percent.

Eliminate Slippery Floors

If your floor seems slippery, check for the source of the dust. Low humidity, space under outside doors, dirty vents or furnace filters and tracked-in mud can all create dust. Oily residue from nearby rugs, hallways, wrestling mats or walk-off mats can also cause a floor to become slippery.