

To Test for an Acrylic Finish

- ① Find an inconspicuous area in the room and identify spot with tape marker.
- ② It is recommended that more than one area is tested.
- ③ Apply a few drops of the test solution on the floor and wait 30 seconds.
- ④ Wipe off solution with a paper towel and observe spot, use flashlight if needed.



A noticeable difference in sheen indicates an acrylic finish is most likely present. **DO NOT COAT OVER AN ACRYLIC FINISH!**

PLEASE NOTE! Results may vary and may not be as dramatic as shown. When in doubt, **DO NOT COAT!**



No change in sheen on the appearance of the floor indicates acrylic wax is most likely **NOT** present.

Acrylic Test Solution

DANGER: CORROSIVE. Causes burns. Vapors harmful. Harmful if swallowed. Avoid contact with skin and eyes. Wear suitable gloves. KEEP OUT OF REACH OF CHILDREN. For Industry Use Only.

FIRST AID: Remove contaminated clothing immediately. **SKIN AND EYES:** Flush skin and eyes immediately with large quantities of water for at least 15 minutes. Seek immediate medical attention. **INGESTION:** If swallowed, contact a poison control center immediately for treatment advice. Have conscious person take sips of water if able to swallow. Never give anything by mouth to an unconscious person. Do not induce vomiting unless instructed to do so by poison control center or doctor. **INHALATION:** Remove to fresh air. If not breathing, call 911 or ambulance, then administer artificial respiration. SEE MATERIAL SAFETY DATA SHEET.