

Floor Polish Remover

Acrylic Floor Polishes are often used to rejuvenate hardwood floors. These coatings cause uneven or unsightly appearance issues over time and must be removed in order to successfully apply professional urethane coatings. If the Acrylic Test Kit (B9166) has determined that an acrylic floor polish is present, use Basic® Coatings Dissolver™ Floor Polish Remover to strip the acrylic floor polish from the hardwood floor.

FEATURES

- Low foaming
- Low odor
- Easy to use

PROPERTIES

Color	Water White
Fragrance	Mild
pH Concentrate	10.5 – 11.0
pH at Dilution	10.0
Packaging.....	Case/4 – 1 US gallon (3.78 L)

DIRECTIONS FOR USE

Read the entire label before using this product.

FLOOR POLISH REMOVAL PROCEDURE:

NOTE: During the stripping process floors can become extremely slippery. Please use caution.

1. To prepare the floor for the cleaning process vacuum or sweep loose dirt from the floor and pay special attention to corners.
2. Always mix Dissolver™ 1:5 with cool water for best results.
3. Use a pump sprayer or Dirt Dragon™ solution wand to apply a thin layer of Dissolver™ Solution to the floor. Be careful not to apply too much solution.
4. Work in small areas around 50 sq. ft.
5. Let the Dissolver™ Solution dwell for no more than 1 minute of contact time. Dissolver™ will begin to emulsify the floor polish.
6. Scrub the area with the Dirt Dragon™ and diluted Dissolver™ and remove the emulsified stripper solution.
7. Manual agitation with a non-abrasive scrubbing pad may be needed for heavy floor polish buildup.
8. Repeat this process in small areas until all floor polish has been removed before moving on to the next area.

9. Retest the floor with the Acrylic Wax Test Kit to make sure that all floor polish has been removed from the floor.
10. Rinse the floor with the Dirt Dragon™ and Squeaky™ to neutralize the floor and prepare it for coating.
11. Allow the floor to dry.
12. Coat the floor with Hardwood Floor Refinisher.

ADDITIONAL PRODUCT USE: This product can be used to remove multiple coats of water-based acrylic and urethane fortified floor finishes from all types of resilient tile and hard surfaces. Not recommended on linoleum or sheet vinyl floors. Color bleeding or discoloration may occur on linoleum, rubber tile, or asphalt tile. Apply solution liberally to floor surface. Allow 3-5 minute contact time. Be sure to keep surface wet at all times. Agitate with a low speed rotary machine, automatic scrubber or stripping machine. Pick up solution with a wet vacuum, automatic scrubber or mop and bucket and thoroughly rinse the floor.

PRECAUTIONS

Keep out of reach of children. For industry use only. **WARNING:** SEVERE SKIN AND EYE IRRITANT. VAPORS HARMFUL IF INHALED. Contains Benzyl Alcohol. Harmful if absorbed through skin. Wear gloves and splash goggles. Avoid contact with eyes, skin, and clothing. Use only with adequate ventilation. **FIRST AID:** Removed contaminated clothing immediately. **SKIN:** Flush area with large quantities of water for 15 minutes. Seek medical attention if irritation persists. **EYES:** Flush eyes with large quantities of water for 15 – 20 minutes. Seek immediate medical attention. **INHALATION:** Remove to fresh air. If not breathing, call 911 or an ambulance, then administer artificial respiration. **INGESTION:** If swallowed, contact a poison control center immediately for treatment advice. Do not induce vomiting unless advised to do so by poison control center or doctor. Never give anything to an unconscious person to ingest.

Obligation Of Manufacturer/Seller

The following is made in lieu of all warranties expressed or implied: Seller's and manufacturers' only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for injury, loss or damage, direct or incidental or consequential, arising out of the use of or the inability to use the product. Before using, the user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers of seller and manufacturer.