

Polyurethane Quick Dry Sealer for Wood Floors

Basic Coatings' Quick Dry Sealers are oil-modified urethanes designed to penetrate and seal bare wood surfaces quickly before finishing. Quick Dry Sealers leave a clear high film build layer that is typically ready to sand in four to six hours.

FEATURES

- Excellent Penetration into Bare Wood
- Easy Application
- Light in Color
- Contains No Stearates
- Available in 5 gallon pails

RECOMMENDED USES

- Basketball, Volleyball and Racquetball Courts
- Multipurpose Rooms, Stages and other Recreational Wood Floors
- Ideal for Enhancing the Natural Beauty of Wood Floors

RECOMMENDED SYSTEMS

New Installations/Newly Sanded Floors.....2 coats BasicCoatings' Quick Dry Sealer and 2 coats of a Basic Coatings' finish

OVER STAINS AND GAME LINE PAINTS

For Stains: Allow stains to dry per manufacturer's directions or longer depending on environmental conditions. Apply 2 coats of a Basic Coatings' Quick Dry Sealer and 2 coats Basic Coatings' finish.

For Game Line Paints: Please refer to Basic Coatings Technical Bulletin, *Approved Game Line Paints and Procedure*, for proper application and a current list of approved paints.

Note: A TEST BOARD IS RECOMMENDED WITH ANY STAIN/GAME LINE PAINT TO INSURE COMPATIBILITY AND COLOR ACCEPTANCE.

PROPERTIES	Quick Dry Sealer	Quick Dry Sealer 350
Color	Slight Amber	Slight Amber
Solid Content	35%	30%
Viscosity (cps)	15	15
VOC	<550 g/L	<350 g/L
Flash Point	100°F	57°F
Dry Time - Recoat	4 - 6 hours	4 - 6 hours
Coverage	300 - 600 sq. ft. / Gal (8 - 15 sq. M/L)	300 - 600 sq. ft. / Gal (8 - 15 sq. M/L)
Clean Up	Mineral Spirits	Mineral Spirits
Storage	Do not store above 120°F (49°C)	Do not store above 120°F (49°C)
Packaging	5 US gal (18.9 L)	5 US gal (18.9 L)
Application	Basic Coatings' T-bar applicator, lamb's wool applicator, or brush	

QUICK DRY SEALER

SURFACE PREPARATION

1. For new installations, refer to NWFA/MFMA specifications and accepted procedures for acclimation of the wood, floor preparation, and sanding.
2. Before sanding, clean the floor using Basic Coatings' Squeaky Cleaner following label instructions. Cleaning should be done to remove contaminants from the floor.
3. Sand floors using accepted NFWA/MFMA procedures. All old finish must be removed. A NIOSH dust mask should be worn during sanding.
4. Finish sanding with new 120-grit screens is recommended.
5. Vacuum. Tack the floor with 3-4 clean terry cloth tack towels dampened with mineral spirits to remove all dust caused by the sanding and screening process. Tack until no residue collects on the towels. Allow the floor to dry with good ventilation.

FINISH APPLICATION

Always maintain adequate ventilation during all phases of the coating and drying process.

1. Stir product well before application.
2. Using Basic Coatings' Applicator or lamb's wool applicator, apply Quick Dry Sealer at the recommended coverage rate. Apply with the grain.
3. Allow to dry, times will vary depending on conditions, usually 4 to 6 hours. Use air blowers to dry corners and dead air spots thoroughly.
4. Abrade floor with new 100 to 120 grit screens is recommended.
5. Vacuum. Tack with 3 - 4 clean terry cloth tack towels dampened with virgin mineral spirits to remove dust. Tack until no dust residue collects on the towels. Allow the floor to dry with good ventilation.
6. Apply second coat or finish coat in the same manner or following manufacturers recommended instructions.

DRY TIME

Typical dry time is 4 to 6 hours depending on environmental conditions. Allow longer dry times in low temperature or high humidity environments.

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. FOR PROFESSIONAL USE ONLY.

CAUTION! COMBUSTIBLE. VAPOR AND SPRAY MIST HARMFUL. CONTAINS MINERAL SPIRITS. MAY CAUSE DIZZINESS, HEADACHE OR NAUSEA. CAUSES IRRITATION.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Harmful or fatal if swallowed. Keep away from heat, sparks and flame. Do not smoke. Extinguish all pilot lights and turn off heaters, non-explosion-proof electrical equipment and all other sources of ignition until vapors are gone. Prevent build-up of vapors. Use with adequate ventilation. Do not breathe vapors, dust or spray mist. Wear an appropriate, properly fitted respirator (NIOSH approved) during and after application unless air monitoring demonstrates vapor mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use. Provide fresh

air ventilation during and after application. Wear protective clothing. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. In case of spillage, absorb and dispose of in accordance with federal, state and local applicable regulations. To avoid spontaneous combustion, soak oil rags and waste daily in water-filled metal containers. Do not store above 100°F (38°C).

FIRST AID: If swallowed, call a physician immediately. Do NOT induce vomiting. If affected by inhalation of vapor, remove to fresh air. If breathing is difficult, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for 15 minutes and call a physician. For skin, wash thoroughly with soap and water.

OBLIGATION OF MANUFACTURER

The following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, the user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers of seller and manufacturer.

