



BID SPECIFICATIONS

PROPERTIES

StreetShoe NXT - Specifications as follows: Gymnasium water-based floor finish, two-part system in five-gallon containers as per the following specifications. Product shall be cross-linked with Polyfunctional Aziridine, water-based urethane/acrylic system with a solids content of 31% NVM or higher. The maximum VOC requirement is to be added when federal, state or local restrictions apply. Batch numbers must appear on the outside of each container. Label shall state usage per square foot per gallon.

Ease of application shall be tested by using the manufacturer's recommended applicator. The material shall be workable so the working edge shall not dry or become tacky and that the next width can be applied without difficulty. When an entire floor has been completed using normal methods, there shall be no visible lap marks or other defects.

Order Number	B1664-0512
Description	StreetShoe NXT – Waterbased Wood Floor Finish
Cross-linked	Yes - Aziridine
Color (Dried Film)	Crystal Clear
Color (Liquid)	Milky White
Coverage	550 - 700 sq. ft./gal
Drying Time	2-3 hours per coat
Recoat time	Recoat within 24hrs
Slip Resistance (ASTM D2047-04)	Meets or exceeds 0.5 coefficient of friction
Viscosity	75 - 100 centipoise
Freeze/thaw Stability	3 cycles
Pot life	24 hours
VOC	<275 g/L
Shelf Life	1 year
