

Water-Based Wood Floor Sealer

GameDay™ Sealer is a premium, clear, one-component waterbased sealer designed for use on sport flooring.

RECOMMENDED USES

GameDay™ Sealer is a premium, commercial-grade, one-component, water-based sealer designed for high-wear and athletic wood floor applications. Ideal for sport wood flooring systems.

PROPERTIES

Color in Container.....	Clear
Solids Content.....	28 +/- 1%
VOC.....	Does not exceed 50 grams/liter
Dry Time.....	Minimum 2-3 hours
Clean Up.....	Water
Coverage.....	450-550 sq. ft. / Gallon
Stability.....	1 year shelf life under proper storage conditions
Storage.....	Do not store above 120° F (49° C) Do not store below 35° F (2° C)
Packaging.....	5 US gallon plastic pails

APPLICATION

Read Technical Data Sheet (TDS) and Safety Data Sheet (SDS) before use. Use appropriate PPE. Test in an inconspicuous area prior to full application. Follow NWFA/MFMA standards and flooring manufacturer recommendations.

RECOMMENDED APPLICATORS

T-Bar/Pad, Roller, Paint Pad, or Brush can be used.

MIXING

Use a stir stick, or rock container several times, to thoroughly mix and re-disperse any settlement. Alternatively, shake well before using – then set aside for at least 20-30 minutes prior to use. It is important to stir (not shake) from time to time to prevent settling.

WATER ADDITION: Up to 12 oz potable water per gallon may be added to improve flow and leveling, especially in high temperatures or low humidity.

SURFACE PREPARATION

- Sand floors per NWFA/MFMA guidelines.
- After final sanding, record moisture readings to establish a baseline.
- Ensure moisture levels are within acceptable regional limits.
- Vacuum thoroughly and tack with clean, dry towels.

APPLICATION GUIDELINES

- Maintain proper temperature and ventilation.
- Restrict airflow during application to prevent premature drying.
- Measure and record moisture content in multiple areas.
- Pre-dampen applicators and remove excess water.

FOR NEW / NEWLY SANDED FLOORS

Apply 1–2 coats of GameDay Sealer, followed by 2 coats of approved Basic Coatings® water-based finish.

APPLICATION METHODS

T-BAR APPLICATION: Pour a 4" line along the starting wall and pull with the grain, maintaining a wet edge. Feather turns and touch up missed areas immediately.

ROLLER APPLICATION: Using a clean, pre-dampened microfiber roller, apply finish in the direction of the wood grain.

DRYING & RECOATING

Allow 30–45 minutes to level. Increase airflow after leveling to promote drying. After 2–3 hours, re-check moisture content. If not at baseline, allow additional dry time.

Abrade between coats if debris is present or if more than 24 hours has elapsed using 180–240 grit. Vacuum and tack between coats. Apply compatible finish once moisture content is acceptable.

Continued on page 2



APPLICATIONS OVER STAINS

Apply only over compatible stains in accordance with the stain manufacturer's instructions. Allow stains to dry completely before sealing. Dry time is affected by stain solids, wood species and porosity, temperature, humidity, airflow, and other jobsite conditions. Always perform an adhesion test in an inconspicuous area prior to full application.

CLEAN-UP

Clean application tools immediately after use with water.

DRY/CURE TIME

Allow at least 2-3 hours between coats. Once you increase air flow, keep air movement for several hours to ensure proper curing. In general, light foot traffic after 24 hours is acceptable. Furniture can be carefully replaced, however finish is susceptible to marring and scratching until the finish is fully cured – approximately 7 days. Do NOT place carpet, rugs, or cover the finish for at least two weeks after the finish has dried.

COVERAGE

Average of 450 – 550 sq ft/gal (11 – 13 sq m/l), depending on wood flooring species, porosity, and other jobsite conditions.

LIMITATIONS

Do not apply over acrylic or waxed surfaces.

FLOOR CARE

Basic Coatings recommends using a NWFMA/MFMA/Industry Certified Professional. Apply approved Basic Coatings waterbased wood finish per directions.

STORAGE

Bring to room temperature and mix thoroughly before using. Do not store above 120°F (49°C). KEEP FROM FREEZING.

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. FOR PROFESSIONAL USE.



WARNING! CAUSES SERIOUS EYE IRRITATION. Wear eye or face protection: Recommended: safety glasses. Wash hands thoroughly after handling. Keep closures tight and upright to prevent leakage. Keep container closed. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

FIRST AID: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

OBLIGATION OF MANUFACTURER

The following is made in lieu of all warranties, expressed or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, the user shall determine the suitability of the product for the intended use and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers of seller and manufacturer.

